



青岛市平度宏华橡胶厂

工厂地址：中国山东省青岛市平度市崔家集镇宏华橡胶工业园 266726
 国内销售电话：0532-82397777 0532-82395555
 国内销售传真：0532-82399999
 国外销售电话：0086-532-85822568 85820926 67708486
 国外销售传真：0086-532-85820926
 工厂网址：www.honghuatyre.com

QINGDAO HONGHUA TYRE FACTORY

Factory Add.: Honghua Rubber Park, Cuijiaji Town of Pingdu, Qingdao China 266726
 Exp. Add.: 13Y Jinfu Mansion(B), 22 Shandong Road, Qingdao China 266071
 Tel: 0086 532 85822568 85820926 67708486
 Fax: 0086 532 85820926
 E-mail: Liu@honghuatyre.com
 Web: http://www.honghuatyre.com http://qdhonghua.en.made-in-china.com

ROCKBUSTER®

PROFESSIONAL TYRE MANUFACTURER SINCE 1994



TYRE BROCHURE 2019-2020



QINGDAO HONGHUA TYRE FACTORY
 青岛市平度宏华橡胶厂



总经理：张永军
GENERAL MANAGER: YONGJUN ZHANG



FACTORY ENVIRONMENT

Company Introduction

Established in October, 1994, Qingdao HongHua Tyre Factory locates itself in the famous touring city of Qingdao. With excellent manufacturing machines and a whole team of first-class professional technicians, HongHua has developed itself into a Top Five professional bias tyre factory in China. With over 700 staffs, and covering 160,000 square meters, We have reached an annual output value of over \$80 million.

Our products range covers OTR Tyre, Industrial Tyre, Solid Tyre, Military Tyre, Mining Tyre, Agricultural Tyre, Speciality Tyre and Truck & Trailer Tyre etc..

Qingdao Honghua Tyre Factory managed to go through the ISO9001, ISO14001, OHSAS18001, CCC, DOT such certificates, and Smithers Test & Reach Test. We have the good reputations in market and bank. We are the SGS/BV Certified factory in China also.

Benefiting from practicing district agency distribution mode, We have successfully established an entire sales network spreading all over the country. Now with ROCKBUSTER & ROADBUSTER brands, by continuous innovating and advancing, we are making Qingdao HongHua a worldwide famous factory in the tyre market.

After 24 years efforts, Qingdao HongHua Tyre is eager to provide quality good products and services for any domestic and international customers. We would like to sincerely appreciate any friends visiting here. WE QUALIFY YOUR WORK ALWAYS!



MAIN PRODUCTS / 主要产品

- 1-12 ● **OTR TYRE**
工程机械轮胎
- 13-16 ● **FORKLIFT TYRE**
叉车轮胎
- 17-24 ● **SPECIALITY IND TYRE**
特种工业轮胎
- 25-32 ● **SUPER SOLID TYRE**
实心轮胎
- 33-46 ● **AGRICULTURAL TYRE**
农业轮胎
- 47-52 ● **MINING TYRE**
矿山轮胎
- 53-56 ● **INDIAN PATTERNS TYRE**
印度花纹轮胎
- 57-64 ● **TRUCK TYRE**
卡车轮胎

PRODUCT BRANDS / 产品商标

ROCKBUSTER[®]

ROADBUSTER **HIMILE**

 **钢铁轮胎**
STEEL TYRES

 **欧美亚**

 **FELDE** 菲力得

CERTIFICATES / 企业认证



NOM

SGS

REACH
SVHC



SMITHERS
RAPRA



OTR TYRE

工程机械轮胎



<http://www.honghuatyre.com>



H108A L-3/E-3 GENERAL BLOCK (S TREAD) 普通花纹块工程机械轮胎

Specially designed for cut and heat resistant compound.
Regular type of tread pattern suitable for hard rock surface and haulage service.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
14.00-24	16	25	10.0	375	1370	4000	7300	375	550	TT/TL	H108A L-3 E-3
	20					4625	8500	475	700		
	24					5150	9500	575	850		
	28					5600	10000	650	925		
16.00-24	20	28	11.25/2.0	430	1495	5450	9750	400	550		
	24					6000	10600	475	650		
	28					6700	11500	575	750		
	32					7300	12500	650	875		
17.5-25	16	28	14.00/1.5	445	1350	4250	7300	300	475		
	20					5000	8250	400	575		
20.5-25	20	30	17.00/2.0	520	1490	6000	9500	325	450		
	24					6700	10300	400	525		
	28					7500	11500	475	625		
23.5-25	20	33	19.50/2.5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		
	28					8750	13600	400	550		
26.5-25	28	35	22.00/3.0	675	1750	10000	15500	350	475		
	32					11200	17000	425	550		
29.5-25	28	38	25.00/3.5	750	1875	11500	17500	325	425		
	34					12500	19000	375	500		
Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
16/70-24	14	24.5	13 (SDC)	410	1175	5600		450		TT	H108A L-3 E-3
16/70-20	14	24	13 (SDC)	410	1075	5150		450			
	18					5800		550			
16/70-16	10	22	10.00G	335	910	1600		280			
14/90-16	10	16	7.0N	270	882	1530		350			
12.00-16	12	17	6.5H	255	890	1600		420			
8.25-16	8	16	6.5	235	865	1530		300			
7.50-16	8	16	5.5	215	815	750		150			



H108AE L-3/E-3 GENERAL BLOCK (ECOTYRE) 普通花纹块工程机械轮胎 (经济型)

Specially designed for wheel loader and earthmover working in good road condition.
It is economic type for users.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
17.5-25	16	26.5	14.00/1.5	445	1350	4250	7300	300	475	TT/TL	H108AE L-3 E-3
	20					5000	8250	400	575		
20.5-25	20	28	17.00/2.0	520	1490	6000	9500	325	450		
	24					6700	10300	400	525		
23.5-25	20	30	19.50/2.5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		

H108B L-3/E-3 LARGE BLOCK (S TREAD) 大块花纹工程机械轮胎

Optimized pattern design for mining and quarrying operations.
Excellent abrasion.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
17.5-25	16	28	14.00/1.5	445	1350	4250	7300	300	475	TT/TL	H108B L-3 E-3
	20					5000	8250	400	575		
23.5-25	20	33	19.50/2.5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		
	28					8750	13600	400	550		

H108C NEW L-3/E-3 LOADER MASTER(Z TREAD) Z型块状工程机械轮胎 (龙工型)

New Z tread tyre for low intensity application of Loader/Earthmover/Grader.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
16.00-25	28	28.5	11.25/2.0	430	1495	6700	11500	575	750	TT/TL	H108C L-3 E-3
	32					7300	12500	650	875		
	36					7750	13600	725	975		
	40					8200	14500	800	1075		
18.00-25	32	31.5	13.00/2.5	500	1615	8750	15000	575	750		
	36					9250	16000	625	850		
	40					9750	17000	700	950		
	44					10500	18000	775	1030		
15.5-25	12	24.5	12.00/1.3	395	1275	3250	5600	250	400		
	16					3850	6750	325	525		
17.5-25	16	28	14.00/1.5	445	1350	4250	7300	300	475		
	20					5000	8250	400	575		
20.5-25	20	30	17.00/2.0	520	1490	6000	9500	325	450		
	24					6700	10300	400	525		
	28					7500	11500	475	625		
	32					8200	12500	525	700		
23.5-25	20	33	19.50/2.5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		
	28					8750	13600	400	550		
26.5-25	28	35	22.00/3.0	675	1750	10000	15500	350	475		
	32					11200	17000	425	550		
29.5-25	28	38	25.00/3.5	750	1875	11500	17500	325	425		
	34					12500	19000	375	500		
16/70-16	10	19	10.00G	335	910		1600		280	TT	
16/70-16	10	22	10.00G	335	910		1600		280		
20.5/70-16	10	19	10.00G	335	910		1600		280		

H108CE NEW L-3/E-3 LOADER TYRE Z TREAD (ECOTYRE) Z型龙工花纹工程机械轮胎 (经济型)

NEW Z tread tyre for wheel loader and earthmover working in good road condition.
It is economic type for users.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
17.5-25	16	27	14.00/1.5	445	1350	4250	7300	300	475	TT/TL	H108CE L-3 E-3
	20					5000	8250	400	575		
20.5-25	20	28	17.00/2.0	520	1490	6000	9500	325	450		
	24					6700	10300	400	525		
23.5-25	20	30	19.50/2.5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		

H108D L-3/E-3 SNOW STAR SPECIAL (ANTI-SKIDDING) 冰雪类似路面专用工程机械轮胎 (防滑专用)

Suitable for snow & ice and similar road condition where need good anti-skidding ability.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
17.5-25	16	28	14.00/1.5	445	1350	4250	7300	300	475	TT/TL	H108D L-3 E-3
	20					5000	8250	400	575		

H109 IND-3S SUPER EXTRA SLICK 工矿用光面平花工程机械轮胎

Suitable for loader and dozer.

Special compound and smooth pattern design is suitable for heat and cut resistant.

Smooth tread with a reinforced sidewall protector for hard working area and underground mining.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
17.5-25	16	30	14.00/1.5	445	1350	7300	475	TT/TL	H109 IND-3S
	20					8250	575		
23.5-25	20	36	19.50/2.5	595	1615	10900	375		
	24					12500	475		
	28					13600	550		

H165 G-2/L-2 SUPER GRADER LOADER SPECIAL 超强平地机和装载机工程机械轮胎

Suitable for wheel loader with extra deep tread and cut resistant compound for rocky surface and mining service.

Excellent traction and stability comfortable / Long life tread design.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg) @ 40km/h	Pressure (kpa) @ 40km/h	Type	Code
13.00-24	12	24	8.00TG	335	1280	2725	300	TT/TL	H165 G-2 L-2
	16					3200	400		
14.00-24	12	25	8.00TG	360	1350	3450	325		
	16					3650	375		

H166 IND-3/E-3 OUTSTANDING QUALITY MINING & PORT EXTRA 港口、矿山特制工程机械轮胎

Suitable for use in port and mining for long mileage.

Specially designed pattern with extra strong tread and reinforced sidewall protector.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
16.00-25	28	32	11.25/2.0	430	1550	6700	11500	575	750	TT/TL	H166 IND-3 E-3
	32					7300	12500	650	875		
	36					7750	13600	725	975		
40	8200	14500	800	1075							
18.00-25	32	36	13.00/2.5	500	1675	8750	15000	575	750		
	36					9250	16000	625	850		
	40					9750	17000	700	950		
	44					10300	18000	775	1050		
18.00-33	32	36	13.00/2.5	500	1820	10000	17500	575	750		
	36					10600	18500	625	850		
	40					11100	20000	675	950		
21.00-25	40	43	15.00/3.0	570	1750	11800	20600	625	825		



H167 L-5 EXTRA HIGH TREAD (ROCK SERVICE) 超加深花纹工程机械轮胎

Suitable for wheel loader with extra deep tread and cut resistant compound for rocky surface and mining service.

Excellent traction and stability comfortable / Long life tread design.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
17.5-25	20	63.5	13.00/1.5	445	1400	8250	575	TT/TL	H167 L-5
	24					8950	650		
20.5-25	20	69	17.00-2.0	520	1560	9500	450		
	24					10300	525		
23.5-25	20	78	19.5/2.5	595	1675	10900	375		
	24					12500	475		
	28					13600	550		
26.5-25	24	87	22.00/3.0	675	1800	14000	400	TL	
	28					15500	450		
	32					17000	525		
29.5-25	28	95	25.00/3.5	750	1920	17500	425		
	34					20000	525		

H168 G-2/L-2 SUPER GRADER LOADER SPECIAL 超强平地机和装载机工程机械轮胎

Suitable for wheel loader with extra deep tread and cut resistant compound for rocky surface and mining service.
Excellent traction and stability comfortable / Long life tread design.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg) @ 40km/h	Pressure (kpa) @ 40km/h	Type	Code
13.00-24	12	24	8.00TG	335	1280	2725	300	TT/TL	H168 G-2 L-2
	16					3200	400		
14.00-24	12	25	8.00TG	360	1350	3450	325		
	16					3650	375		
16.00-24	12	28.5	10.00VA	470	1460	3650	225		
	16					4500	325		
17.5-25	16	26	14.00/1.5	445	1350	3350	275		
	20					3650	325		
20.5-25	16	28.5	17.00/2.0	575	1490	4000	225		
	20					4500	275		

H169 E-7 HEATMASTER SAND/DESERT TIRE 耐热大师系列沙漠轮胎

The combination of wide tread, round shoulder and streamlined pattern design provides stable ride, good floating force, excellent steering ability on sand ground road surface.
With HEATMASTER compound for desert application.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
8.25-16	8	10	6.0	850	225	1500	245	TT	H169 E-7
9.00-15	8	10	5.50F	840	235	1650	245	TT/TL	
9.00-16	8	10	6.50H	860	245	1320	310	TT/TL	
9.00-17	8	10	7J	880	245	1320	310	TT/TL	
16.00-16	16	8	6.50H	1100	355	4000	246	TT	
14.00-20	18	10	10.00W	1207	355	4125	245	TT/TL	
16.00-20	16	14	10.00W	1323	419	5450	245		
21.00-25	16	14	15.00/3.0	1699	599	10000	245		
29.5-25	28	21	25.00/3.5	1820	687	10000	240		

H176 E-2 HEAVY COUNTRY CROSS TIRE (SUPER MILITARY APP.) E-2 重性越野轮胎 (军工适用)

Super country-cross pattern is suitable for heavy trucks and other machines.

Military tech design can support using in terrible conditions such as desert, grass, forest, mountain road etc.



Size	PR	S.R.	S.W. (mm)	O.D. (mm)	Pressure (kpa)	Loading (kg)	Max Speed (km/h)	Type	Code
1500x600-635	14	500x635	600	1500	380	5750	60	TT	H176 E-2
	22				550	7050	60		
1600x600-685	24	500x685	600	1600	440	7900	60		

H178 R-3/C-2/E-7 MULTI-PURPOSE FLOATION TIRE R-3/C-2/E-7 多用途浮力型轮胎 (压路机及沙漠车辆用胎)

Wide Section for good flotation force and steering ability.
Special for desert transportation and road compactor application.



Size	PR	S.R.	S.W. (mm)	O.D. (mm)	Pressure (kpa) @ 10km/h	Loading (kg) @ 10km/h	Type	Code
23.1-26	12	DW20	595	1500	200	5150	TT/TL	H178 R-3 C-2 E-7
	14				230	5600		
	16				260	6150		



FORKLIFT TYRE

叉车轮胎



<http://www.honghuatyre.com>

H989 INDUSTRIAL MASTER (NHS)

常规花纹工业叉车轮胎

Developed for heavy use on forklifts and other industrial vehicles. With its wide and extra deep tread provides stronger traction, longer life and puncture resistance.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Pressure (kpa)	Max Loading(kg)				Code	
							25km/h		35km/h			
							Load	Rota	Load	Rota		
8.25-15	14	18	6.5	840	235	830	3775	3185	3505	2800	H989 NHS	
	16						925	4050	3450	3600		3010
28*9-15 (8.15-15)	14	19	7.0	710	220	970	3050	2575	2835	2265		
	16						1000	3115	2630	2895		2310
8.25-12	12	18	6.5	765	235	720	3060	2585	2840	2270		
7.00-12	12	13	5.00S	676	190	860	2375	2005	2205	1765		
	14						1000	2590	2190	2405		1925
6.50-10	10	12	5.00F	590	175	790	1655	1400	1540	1230		
	12						1000	1895	1600	1765		1410
7.00-9	10	13	5.00S	590	190	860	1995	1685	1850	1480		
6.00-9	10	11	4.00F	540	160	860	1505	1275	1400	1120		
	12						1030	1675	1415	1560		1245
5.00-8	10	11	3.50D	470	137	1000	1150	970	1065	850		
16*6-8	10	13	4.33R	425	152	860	1085	920	1010	805		
							760	1310	1105	1215	970	
18*7-8 (180/70-8)	14	15	4.33R	465	173	970	1505	1270	1400	1120		
	16						1000	1695	1450	1640	1260	
	620						1545	1305	1435	1145		
21*8-9 (200/75-9)	10	15	6.00E	535	200	1000	2040	1725	1895	1515		
	14						760	2345	1980	2175	1740	
23*9-10	12	16	6.50F	595	225	900	2585	2185	2405	1920		
	14						1030	2810	2370	2610	2095	
	16											
Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Pressure (kg)	Max Loading (kpa)	Type	Code			
300-15	18	21	8.0	848	300	830	5530	TT	H989 NHS			
	20						930			5940		
12.00-20	18	29	8.5	1135	315	790	6335					
	20						900			7400		
10.00-20	16	28	7.5	1078	278	790	6030					
	18						890			6475		
9.00-20	14	26	7.0	1025	259	760	5195					
	16						860			5595		
7.50-15	14	21	6.0	780	215	925	3375					
	16						1000			3550		
7.00-15	12	21	5.5	750	200	860	2870					
	14						1000			3140		
27X10-12	14	16	8.00G	690	255	860	3285					
	16						1000	3585				

TW898 EXTRA POWER STRONG INDUSTRIAL

超级宽厚花纹工业叉车轮胎

Pattern design with wide contact area increases traction. Reinforced tie bar between the zig-zag pattern. New compound for outstanding durability / longer life.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
8.25-15	16	25	6.50	845	242	4470	880	TT	TW898 IND
7.50-16	16	22	6.00GS	810	212	3870	880		

H990 XTRA WALL AND MASSIVE TREAD BLOCK

新宽厚花纹工业叉车轮胎

New pattern design supports longer working life. Special compound could be used in much more hard working sites. Non-symmetric tread offers more traction power and better wear-ability.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
8.25-15	16	22	6.50	840	242	4470	880	TT	H990 NHS
	14					3145	780		
28X9-15	16	22	7.00	713	220	3400	880		
	7.00-12					14	20		
6.50-10	12	21	5.00	590	185	2095	880		
7.00-9	10	19	5.00	590	192	1995	860		
6.00-9	12	18	4.00	540	168	1730	835		
5.00-8	10	16	3.50	470	138	1305	880		
	14					1505	970		
18X7-8	16	18	4.33R	465	173	1695	1000		

DT1000 SUPER DEEP TREAD & WIDE CROWN SERIES

超深花纹工业叉车轮胎

Developed for heavy use on forklifts and other industrial vehicles. With its wide and extra deep tread provides stronger traction, longer life and puncture resistance.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
8.25-15	16	33.5	6.50	851	246	4470	880	TT	DT1000 NHS
7.00-12	14	33.5	5.00	680	200	3085	980		
6.50-10	12	31	5.00	599	185	2095	880		



SPECIALITY IND TYRE

特种工业轮胎



<http://www.honghuatyre.com>

AS2000 L-2 URBAN INDUSTRIAL L-2 城市用挖掘机、工业拖车轮胎

Developed for urban excavator and industrial trailer vehicles, by new compound for outstanding durability. Extra deep tread provides longer life and puncture resistance. Reinforced tie bar between the zig-zag block pattern.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
9.00-20	16	28	7.00	1025	260	4060	740	TT	AS 2000 L-2 NHS

H966 G-2/L-2/E-2 EXCAVATOR TYRE(X'C) G-2/L-2/E-2 挖掘机轮胎系列

Optimized pattern design for excavator. Excellent abrasion and traction and self-cleaning.



H966A H966B

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 10km/h	Pressure (kpa) @ 10km/h	Type	Code
8.25-20	14	20	6.5	235	992	3865	830	TT	H966A
9.00-20	16	22	7.0	259	1038	4725	860		G-2/L-2/E-2
10.00-20	18	22	7.5	278	1073	5470	890		H966A G-2/L-2/E-2
11.00-20	16	24	8.0	293	1105	5405	760		
	18					6000	825		
9.00-20	16	25	7.0	259	1040	4725	860		H966B G-2

H967 G-2/L-2 EXCAVATOR TYRE (ECO-USE) G-2/L-2 经济型挖掘机轮胎



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 10km/h	Pressure (kpa) @ 10km/h	Type	Code
9.00-20	16	20	7.0	259	1038	4725	860	TT	H967 G-2/L-2
10.00-20	18	20	7.5	278	1073	5470	890		



SKS-1 (R-4) SKS-2 (NEW L-2) SKS-3 (L-5) SKS-4 (PLUS)

SKS-1/2/3/4 SKID STEER TYRE 工业车辆轮胎

Size	PR	Rim	T.D. (mm)	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code	
27X8.5-15	8	7JA	13	215	678	1030	350	TL	SKS-1 R-4	
10-16.5	8	8.25	19	773	264	1880	410			
	10					2135	520			
	12					2375	620			
12-16.5	12	9.75	19	831	307	2865	550			
	14					3075	620			
14-17.5	14	10.5	19	921	349	3875	550			
	14					4565	485			
15-19.5	14	11.75	21	1019	389	4935	550			
	16									
12-16.5	14	9.75	25	842	325	3075	620			SKS-2 NEW L-2
10-16.5	12	8.25	35	785	270	2375	620			SKS-3 L-5
12-16.5	14	9.75	42	845	314	3075	620			SKS-4 PLUS
10-16.5	12	8.25	27	785	270	2375	620			
12-16.5	14	9.75	35	840	315	3075	620			

SKS-1 R-4 STANDARD

Optimized pattern design for loader/grader with excellent traction and self-cleaning in a muddy ground.

SKS-2 NEW L-2 EXTR FLOATING

For loaders and dozers operations on rock, coal and earth. Separate lugs and tapered for greater traction and self-cleaning.

Extra wide tread profile for better land ratio and High floating force.

SKS-3 L-5 EXTRA DEEP

Application to Skid Steer loader and scraper tyre for hard working area. Good wear resistance, with extra deep tread and side-skidding resistance.

SKS-4 PLUS A/T TYRE

For loaders and dozers operations on rock, coal and earth. Extra wide tread profile for better land ratio and High floating force.



SKS-5

SKS-6

SKS-7

SKS-5/6/7 SKIDSTEER TYRE 工业车辆轮胎

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
33X12-16.5	10	14	9.75	310	840	2540	450	TL	SKS-5 Off Road
33X12-16.5	10	14	9.75	310	840	2540	450		SKS-6 Sandtrack
33X12-16.5	10	14	9.75	310	840	2540	450		SKS-7 Turf

H658 R-4 INDUSTRIAL TYRE R-4 特种工业轮胎

Very good traction and better tire life.
Good resistance to tearing and cracking.
Resistance to cuts, abrasions and high load capacity.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
16.9-24	10	27	W15L	430	1323	2230	200	TL	H658 R-4
	12					2440	240		
16.9-28	10	27	W15L	430	1423	2380	200		
	12					2605	240		
18.4-26	10	27	W16L	467	1438	2645	180		
	12					2985	230		
17.5L-24	10	26	W15L	445	1253	1725	190		
	12					1925	250		
19.5L-24	10	27	DW16	495	1328	1925	170		
	12					2145	210		
21L-24	10	29	DW18	533	1388	2090	150		
	12					2410	190		
	16					2795	250		

H659 R-4 TRACTION IMPLEMENT/BACKHOE R-4 特种工业轮胎

Excellent traction and flushing / Good resistance to cracking.
Strengthen and stabilize tread under severe operating condition.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
10.5/80-18	10	22	9	274	1323	1935	370	TL	H659 R-4
	12					2150	430		
12.5/80-18	10	26	9	308	987	2375	310		
	12					2625	370		
	14					2910	430		
	16					3130	490		

H660 R-4 INDUSTRIAL TYRE R-4 特种工业用胎

Very good traction and better tire life.
Good resistance to tearing and cracking.
Resistance to cuts, abrasions and high load capacity.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
19.5L-24	10	27	DW16	495	1328	1925	170	TL	H660 R-4
	12					2145	210		

H661 F-3 INDUSTRIAL FRONT F-3 特种工业轮胎

Husky industrial rib design, wide profile for front backhoe loader service.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30 km/h	Pressure (kpa) @ 30 km/h	Type	Code
11L-15	10	12	8LB	280	810	1190	340	TL	H661 F-3
	12					1355	420		
11L-16	10	12	8LB	280	835	1240	340		
	12					1395	420		

H663 I-1 FARM SPECIALIST IMPLEMENT I-1 农机具轮胎

Multi rib farm tire designed for flotation for use on farm implement, wagons, tanks, carts and other pull behind vehicles.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30 km/h	Pressure (kpa) @ 30 km/h	Type	Code
9.5L-15	8	8	8LB	240	765	1100	280	TL	H663 I-1
	10					1310	340		
11L-15	8	9	W8L	280	775	1130	220		
	10					1285	280		
	12					1345	340		
12.5L-15	8	9	W10L	317	823	1350	220		
	12					1730	330		
	14					1830	360		
11L-16	8	9	W8L	280	800	1175	220		
	10					1340	280		
	12					1515	340		

H664 R-1 TRACTION STAR (IND & AG) R-1 强大牵引力工农业用胎

Best for tractor, telehandler, backhoe loader, compactor. Excellent traction, self-cleaning and cutting resistance



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
15.5/80-24 (400/80-24)	12	35	13.0	394	1262	2900	300	TL	H664 R-1
	16					3350	400		

H665 DEEP R-4 TRACTION STAR 加深 R-4 强大牵引力工农业用胎

Best for tractor, telehandler, backhoe loader, compactor. Excellent traction, self-cleaning and cutting resistance



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
☆ 405/70-20 (16/70-20)	14	37	13.0	407	1076	3250	350	TL	H665 DR-4
☆ 405/70-24 (16/70-24)									



ROCKBUSTER®

SUPER SOLID TYRE

实心轮胎



<http://www.honghuatyre.com>

H991A

XTRA WALL AND MASSIVE TREAD BLOCK SOLID
超强充气式轮辆实心轮胎

High quality raw material support and unique formula design.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial	
					10km/h		16km/h		10km/h	
					Load	Rota	Load	Rota		
300-15 (315/70-15)	29	8.0	838	300	6895	5305	6300	4845	5310	H991A SOLID

H991B

EXCELLENT VIBRATION CONTROL PATTERN SOLID
港口机车专用充气式轮辆实心轮胎

Aggressive pattern for port trailer and forklift.
High load & excellent wear-resistance.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial	
					10km/h		16km/h		10km/h	
					Load	Rota	Load	Rota		
9.00-20	40	6.5	1038	259	6160	5135	5630	4690	4745	H991B SOLID
9.00-20		7.0	1038	259	6365	5305	5815	4845	4905	
10.00-20	40	7.5	1073	278	7075	5895	6460	5385	5450	
10.00-20		8.0	1073	278	7300	6085	6670	5560	5630	
11.00-20	45	7.5	1095	300	7470	6225	6820	5685	5750	
11.00-20		8.0	1095	300	7715	6430	7045	5870	5940	
12.00-20	45	8.0	1180	310	8640	7200	7885	6570	6650	
12.00-20		8.5	1180	310	8920	7435	8140	6785	6865	

H992A

SUPER STRONG LARGE BLOCK SOLID
大块花纹充气式轮辆实心轮胎

Little rolling resistance & low heat generating.
Little energy conservation & strong rockfall resistance.
It's the best choice for balanced forklift and other industrial vehicles.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial	
					10km/h		16km/h		10km/h	
					Load	Rota	Load	Rota		
400-8	20	3.0	423	121	1090	840	995	765	840	H992A SOLID
		3.75	423	125	1175	905	1080	830	910	
5.00-8	24	3.0	469	146	1255	965	1145	880	960	
18*7-8	24	4.33	457	170	2430	1870	2215	1705	1870	
6.00-9	24	4.0	545	160	1975	1520	1805	1390	1520	
6.50-10	28	5.0	597	178	2715	2090	2485	1910	2095	
7.00-9	28	5.0	578	185	2670	2005	2440	1875	2055	
7.00-12	29	5.0	683	192	3105	2390	2835	2180	2390	
8.25-12	38	6.5	735	236	3425	2635	3125	2405	2635	
8.15-15 (28*9-15) (225/75-15)	35	7.0	706	225	4060	3125	3710	2855	3125	
8.25-15	38	6.5	847	236	5085	3910	4640	3570	3910	
300-15 (315/70-15)	29	8.0	838	300	6895	5305	6300	4845	5310	

H992B EXTRA POWER STRONG INDUSTRIAL SOLID
小块花纹高档充气式轮胎实心轮胎

High quality raw material support and unique formula design.
The tyre enjoys outstanding performance at all aspects.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial 10km/h	
					10km/h		16km/h			
Load	Rota	Load	Rota							
5.00-8	24	3.0	469	146	1255	965	1145	880	960	H992B SOLID
18*7-8	24	4.33	457	170	2430	1870	2215	1705	1870	
6.00-9	24	4.0	545	160	1975	1520	1805	1390	1520	
6.50-10	28	5.0	597	178	2715	2090	2485	1910	2095	
7.00-9	28	5.0	578	185	2670	2005	2440	1875	2055	
7.00-12	29	5.0	683	192	3105	2390	2835	2180	2390	
8.25-12	38	6.5	735	236	3425	2635	3125	2405	2635	
8.15-15 (28*9-15) (225/75-15)	35	7.0	706	225	4060	3125	3710	2855	3125	
8.25-15	38	6.5	847	236	5085	3910	4640	3570	3910	

H993 PERFECT BALANCE INNOVATIVE TREAD SOLID
均衡型花纹充气式轮胎实心轮胎

High land ratio for longer life.
It's the best choice for balanced forklift and other industrial vehicles.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial 10km/h	
					10km/h		16km/h			
Load	Rota	Load	Rota							
16*6-8	17	4.33	418	162	1545	1190	1410	1085	1185	H993 SOLID
21*8-9	27	6.0	535	207	2890	2225	2645	2035	2230	
23*9-10	26	6.5	595	225	3730	2870	3405	2620	2865	

H994 KING STAR SOLID
超高档实心轮胎

Best cutting resistance.
Expert low rolling resistance.
Longest lifespan.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial 10km/h	
					10km/h		16km/h			
Load	Rota	Load	Rota							
☆ 5.00-8	24	3.0	469	146	1255	965	1145	880	960	H994 SOLID
☆ 18*7-8	24	4.33	457	170	2430	1870	2215	1705	1870	
☆ 6.00-9	24	4.0	545	160	1975	1520	1805	1390	1520	
☆ 6.50-10	28	5.0	597	178	2715	2090	2485	1910	2095	
☆ 7.00-9	28	5.0	578	185	2670	2005	2440	1875	2055	
☆ 7.00-12	29	5.0	683	192	3105	2390	2835	2180	2390	
☆ 8.25-12	38	6.5	735	236	3425	2635	3125	2405	2635	
☆ 8.15-15	35	7.0	706	225	4060	3125	3710	2855	3125	
☆ (28*9-15)										
☆ (225/75-15)										
☆ 8.25-15	38	6.5	847	236	5085	3910	4640	3570	3910	
☆ 16*6-8	17	4.33	418	162	1545	1190	1410	1085	1185	
☆ 21*8-9	27	6.0	535	207	2890	2225	2645	2035	2230	
☆ 23*9-10	26	6.5	595	225	3730	2870	3405	2620	2865	
☆ 9.00-20	40	6.5	1038	259	6160	5135	5630	4690	4745	
☆ 9.00-20		7.0	1038	259	6365	5305	5815	4845	4905	
☆ 10.00-20	40	7.5	1073	278	7075	5895	6460	5385	5450	
☆ 10.00-20		8.0	1073	278	7300	6085	6670	5560	5630	
☆ 11.00-20	45	7.5	1095	300	7470	6225	6820	5685	5750	
☆ 11.00-20		8.0	1095	300	7715	6430	7045	5870	5940	
☆ 12.00-20	45	8.0	1180	310	8640	7200	7885	6570	6650	
☆ 12.00-20		8.5	1180	310	8920	7435	8140	6785	6865	

H992A NON-MARKING SOLID 无痕环保实心轮胎

Environmental friendly.
Static electricity free.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial	
					10km/h		16km/h			
					Load	Rota	Load	Rota	10km/h	
400-8	20	3.0	423	121	1090	840	995	765	840	H992A SOLID
		3.75	423	125	1175	905	1080	830	910	
5.00-8	24	3.0	469	146	1255	965	1145	880	960	
18*7-8	24	4.33	457	170	2430	1870	2215	1705	1870	
6.00-9	24	4.0	545	160	1975	1520	1805	1390	1520	
6.50-10	28	5.0	597	178	2715	2090	2485	1910	2095	
7.00-9	28	5.0	578	185	2670	2005	2440	1875	2055	
7.00-12	29	5.0	683	192	3105	2390	2835	2180	2390	
8.25-12	38	6.5	735	236	3425	2635	3125	2405	2635	
8.15-15 (28*9-15) (225/75-15)	35	7.0	706	225	4060	3125	3710	2855	3125	
8.25-15	38	6.5	847	236	5085	3910	4640	3570	3910	
300-15 (315/70-15)	29	8.0	838	300	6895	5305	6300	4845	5310	

- NON-MARKING SOLID TIRES OF H991A, H991B, H992B, AND H993 ARE AVAILABLE ALSO.
- 我们也可以生产具有H991A, H991B, H992B, 以及H993花纹的无痕环保实心轮胎。
- OTHER COLORS ARE AVAILABLE TOO.
- 可选其他颜色。

TW993 NON-MARKING SOLID FOR AIRPORT WORKING 机场专用无痕环保浅纹实心轮胎

High quality raw material support and unique formula design.
The tyre enjoys outstanding performance at all aspects.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)				Code	
					Forklift					
					10km/h		16km/h			Other Industrial
		Load	Rota	Load	Rota	10km/h				
400-8	4	3.0	326	110	1090	840	995	765	840	TW993

TW994 NON-MARKING SOLID FOR AIRPORT WORKING - SMOOTH 机场专用无痕环保光面实心轮胎

Long life / Low rolling resistance / Environmental friendly.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial	
					10km/h		16km/h			
					Load	Rota	Load	Rota	10km/h	
200-8										TW994

H995 NON-MARKING SOLID WITH WHEEL MOUNTED 无痕环保实心轮胎

Environmental friendly.
Static electricity free.



Size	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Max Loading(kg)					Code
					Forklift				Other Industrial	
					10km/h		16km/h			
					Load	Rota	Load	Rota	10km/h	
406X125										H995



AGRICULTURAL TYRE

农业轮胎



<http://www.honghuatyre.com>



H657-1

H657-2

H657-3

H657-4

H657-5

H657-1/2/3/4/5 R-1 SUPER FARM TYRE FOR DRIVE WHEEL

R-1 人字驱动轮以及前轮用农业轮胎

For general farm tractors.
Provides good cutting resistance and longer lifetime.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
6.00-12	6	20	4.50E	165	640	405	250	TT	H657-1 R-1
6.00-12	6	20	4.50E	165	640	405	250		H657-2 R-1
6.00-12	6	23	4.50E	165	640	405	250		H657-3 R-1
6.00-16	6	24	4.50E	165	745	495	250		H657-4 R-1
7.50-16	6	22	5.50F	205	810	650	210		H657-5 R-1
	8					800	280		



H657-6 R-1 SUPER FARM TYRE FOR DRIVE WHEEL

R-1 人字驱动轮农业轮胎

Tractor tire for drive wheel.
Powerful traction and good cutting resistance.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
11.2-24	10	32	W10	285	1105	1380	300	TT	H657-6 R-1
14.9-24	10	38	W13	378	1265	1990	230		
16.9-30	12	39	W15L	430	1485	2730	240		
16.9-34	10	39	W15L	430	1585	2605	200		
	12					2945	240		
18.4-34	12	36	W16L	467	1655	3375	230		

H657-7 R-1 SUPER FARM TYRE FOR DRIVE WHEEL

R-1 人字驱动轮农业轮胎

Tractor tire for drive wheel.
Good traction and high grip ability.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
7.50-20	6	25.5	5.50F	205	910	760	210	TT	H657-7 R-1
	8					900	250		
8.3-24	6	30	W7	210	995	810	240		
	8					950	300		
9.5-20	8	28	W8	240	950	955	280		
	10					1190	370		
9.5-24	8	31	W8	240	1050	1110	280		
	10					1300	370		
11.2-28	8	35	W10	285	1205	1305	240		
	10					1515	300		

H657-8/10

R-1 SUPER FARM TYRE FOR DRIVE WHEEL
R-1 人字驱动轮农业轮胎

Tractor tire for drive wheel and load wheel.
Excellent traction, self-cleaning and cutting resistance.



H657-8

H657-10

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
8.3-20	6	28	W7	210	895	695	240	TT	H657-8 R-1
	8					880	300		
9.5-20	8	27	W8	240	950	955	280	TT	H657-10 R-1
	10					1190	370		

H657-11/12

R-1 SUPER FARM TYRE FOR DRIVE WHEEL
R-1 人字驱动轮农业轮胎

Tractor tire for drive wheel.
Powerful traction and good cutting resistance.



H657-11

H657-12

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
14.9-26	10	42	W13	378	1315	2055	230	TT	H657-11 R-1
	12					2310	260		
18.4-30	12	35	W16L	467	1550	3180	230	TT	H657-12 R-1
	10					2320	230		
15.5-38	12	34	W14L	395	1570	2700	260		



H657-13



H657-14



H657-15

H657-13/14/15

R-1(LS-1) SUPER TRACTOR & HARVESTER TYRE
R-1(LS-1) 超强拖拉机和收割机轮胎

Tractor/Harvester tire for drive wheel and load wheel.
Excellent traction, self-cleaning and cutting resistance.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
12.4-24	8	36	W11	315	1160	1415	230	TT	H657-13 R-1/LS-1
	10					1650	280		
12.4-28	8	36	W11	315	1260	1510	230	TT	H657-14 R-1/LS-1
	10					1760	280		
14.9-24	10	38	W13	378	1265	1990	230	TT	H657-14 R-1/LS-1
14.9-28	10	38	W13	378	1365	2120	230		
18.4-38	12	41	W16L	467	1755	3575	230	TT	H657-15 R-1/LS-1
15-24	10	37	DW14	410	1330	2800	280		

H657-16 CR-1 FARM TYRE CR-1 农业拖拉机中耕轮胎

Tractor tire for drive wheel with good cutting resistance for longer tire life.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
12.4-48	12	36	W11	315	192	3205	310	TT	H657-16 CR-1

H657-17/18

R-1/HR-1 SUPER FARM TYRE (DEEP TREAD)
R-1/HR-1 加高人字花纹拖拉机轮胎

Specially designed lug profiles for full traction power and self-cleaning.



H657-17

H657-18

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
6.00-12	6	30	4.50E	165	640	405	250	TT	H657-17 R-1/HR-1
6.00-16	6	28	4.50E	165	745	495	250	TT	H657-18 R-1/HR-1

H657-19/20

R-1/HR-1 SUPER FARM TYRE (EXTRA DEEP TREAD)
R-1/HR-1 超加高加宽人字花纹拖拉机轮胎 (水旱两用)

Powerful pattern & Wear resistance.
Longer life & High durability.



H657-19

H657-20

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
6.50-16	6	38	5.00F	180	765	565	250	TT	H657-19 R-1/HR-1
9.5-24	8	42	W8	240	1050	1110	280	TT	H657-20 R-1/HR-1
	10					1300	370		
11.2-24	10	42	W10	285	1105	1380	300		

H657-21

R-1/HR-1 SUPER FARM TYRE (DEEP TREAD)
R-1/HR-1 加高人字花纹拖拉机轮胎

Specially designed lug profiles for full traction power and self-cleaning.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
6.00-16	6	31	4.50E	165	745	495	250	TT	H657-21 R-1/HR-1
6.50-16	6	32	5.00F	180	765	565	250		
7.50-16	6	33	5.50F	205	810	650	210		
	8					800	280		
8.3-20	6	38	W7	210	895	695	240		
	8					880	300		
8.3-24	6	38	W7	210	995	810	240		
	8					950	300		
9.5-20	8	42	W8	240	950	955	280		
	10					1190	370		
9.5-24	8	42	W8	240	1050	1110	280		
	10					1300	370		
11.2-24	10	42	W10	285	1105	1380	300		
	8					1305	240		
11.2-28	10	45	W10	285	1205	1515	300		
	8					1510	230		
12.4-28	10	45	W11	315	1260	1760	280		
	8					1510	230		
13.6-24	10	48	W12	345	1210	1790	250		
	8					2605	200		
16.9-34	12	50	W15L	430	1585	2945	240		
	10					1570	140		
12-38	8	37	DW11	356	1575	1850	180		
	10					1000	140		
11-32	6	33	W10	305	1360	1250	180		
	8								

H657-22 R-2 HARVESTER TYRE R-2 蔗田以及稻田型收割机轮胎

Larger traction tire for drive wheel.
Powerful traction, excellent wear resistance and self-cleaning.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
19.5L-24	12	76	DW16	535	1340	2145	210	TT	H657-22 R-2
18.4-30	12	81	W16L	467	1550	3180	230		
23.1-26	14	89	DW20	587	1652	3970	200		
28L-26	14	89	DW25	715	1615	4245	170		

H657-23 R-1/IR-1 IRRIGATION TYRE R-1/IR-1 人字灌溉农业胎

Special design for irrigation application.
Good self cleaning property and sufficient traction.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
☆ 11.2-24	6	28.5	10	1103	285	1045	180	TT/TL	H657-23 R-1/IR-1
☆ 12.4-24	8	28.5	W11	1160	315	1415	230		
☆ 14.9-24	8	31	13	1265	378	1760	180		

H657-24 M-Z HARVESTER FRONT WHEEL M-Z 收割机前轮轮胎

Comfortable operation.
Longer tyre lifetime.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
12.00-18	10	18	9.00V	325	1085	1800	320	TT	H657-24 R-1/HR-1
	12					2300	420		

H657-25 PR-1 SUPER PADDY FIELD TYRE PR-1 高档水田轮胎

Powerful traction, excellent driving stability and Steering Accuracy.
Longer life and High durability, Wear resistance, Outstanding Cold & Heat resistance.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
6.00-12	6	45.5	4.5E	165	690	425	270	TT	H657-25 PR-1
6.50-16	8	57	5.00F	165	830	565	250		
7.50-16	10	64	5.50F	195	890	750	300		
8.3-20	10	64	W7	210	950	970	270		
8.3-24	10	64	W7	210	1050	1135	270		
9.5-20	10	78	W8	240	1050	1140	240		
9.5-24	10	78	W8	240	1150	1315	240		
11-32	12	90	W10	305	1460	1080	160		
11.2-24	12	83	W10	285	1205	1465	210		
12.4-26	12	86	W11	315	1265	1728	200		
12.4-28	12	86	W11	315	1315	1785	200		
13.6-24	12	90	W12	345	1210	1790	250		
13.6-38	12	90	W12	345	1710	2675	230		
14.9-24	12	90	W13	378	1265	1990	230		
14.9-26	12	90	W13	378	1315	2055	230		
14.9-28	12	90	W13	378	1365	2120	230		
14.9-30	12	95	W13	378	1415	2190	230		
16.9-30	12	95	W15L	430	1485	2730	240		
16.9-34	12	95	W15L	430	1585	2605	200		
18.4-34	12	95	W16L	467	1655	3375	230		
18.4-38	12	95	W16L	467	1755	3575	230		

H657-26 PR-1 SUPER PADDY FIELD TYRE PR-1 高档水田轮胎

Powerful traction, excellent driving stability and Steering Accuracy.
Longer life and High durability, Wear resistance, Outstanding Cold & Heat resistance.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
11-32	12	85	W10	305	1460	1080	160	TT	H657-26 PR-1
13.6-24	12	90	W12	345	1210	1790	250		
14.9-24	12	90	W13	378	1265	1990	230		
14.9-26	12	90	W13	378	1315	2055	230		
14.9-28	12	90	W13	378	1365	2120	230		
14.9-30	12	90	W13	378	1415	2190	230		
16.9-30	12	90	W15L	430	1485	2730	240		
16.9-34	12	90	W15L	430	1585	2605	200		
18.4-38	12	90	W16L	467	1755	3575	230		

H657-27

R-1/HR-1 OVER SIZE AG TYRE FOR DRIVE WHEEL
FIELD & ROAD USE, DOUBLE DUTY

R-1/HR-1 超大尺寸人字驱动轮农业轮胎
田路两用轮胎, 双倍载重保证

Confident grip & good self-cleaning
Extra deep lug depth for long wearing.
Import design.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
☆ 12.4-28	10	39	W11	315	1276	1760	280	TT	H657-27 R-1 HR-1
☆ 13.6-28	10	40	W12	345	1320	1910	250		
☆ 14.9-28	10	40	W13	378	1365	2120	230		
☆ 16.9-30	12	40	W15L	430	1485	2730	240		
☆ 18.4-30 (18.4/15-30)	12	44	W16L	467	1550	3180	230		
☆ 15.5-38	12	42	W14L	395	1570	2700	260		



H889

H206

H207

H208

H889 H206 H207 H208

AG FRONT WHEEL & TRAILER WHEEL
农机车导向轮和拖车轮用轮胎

Long tyre life with wear resistance.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
4.50-16	6	7	3.00D	130	655	400	390	TT	H889
5.00-14	4	7	3.00D	130	620	365	340		
4.50-14	4	7	3.00D	122	606	345	340		
4.00-14	4	7	3.00D	110	590	270	340		
4.50-12	4	6	3.00D	122	550	307	340		
5.00-14	8	9.5	3.00D	130	620	500	420	TT	H206
4.50-14	8	8	3.00D	122	606	400	420	TT	H207
6.00-16	6	8	4.00E	160	740	560	340	TT	H208
5.50-16	6	8	4.00E	150	710	525	370		
5.00-16	6	7.5	4.00E	142	680	500	370		
4.50-16	6	7	3.00D	130	655	400	390		
4.00-14	4	7	3.00D	110	590	270	340		
4.00-12	4	7	3.00D	110	535	250	340		



H209A

H209B

H209A H209B F-2 TRIPLE RIB FARM STEERING F-2 农机车导向轮轮胎

Better Steering with good stability / Self cleaning and damage resistance.
Better tire life / High load capacity.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
11.00-16	10	23	W10L	315	970	1485	310	TT/TL	H209A F-2
10.00-16	10	23	W8L	275	910	1325	340		
7.50-16	8	21	5.50F	205	810	870	370		
5.50-16	6	13	4.00E	150	710	525	370	TT	
5.00-15	6	9.5	4J	140	665	465	420		
4.00-16	4	8	3.00D	110	640	300	340		
4.00-14	4	7	3.00D	110	590	270	340	TT	H209B F-2
☆ 7.50-16	10	18.5	5.50F	205	810	1000	450		



MINING TYRE

矿山轮胎



<http://www.honghuatyre.com>



H988 MINING TRUCK TIRE

常规矿山系列轮胎

For dump trucks on mining and logging service.
Deeper tread pattern for powerful traction and long mileage.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)	Speed Index	Load Index	Code
						Dual	Single				
12.00-20	20	32	8.5	315	1145	3450	4000	810/880	G	151/156	H988
11.00-20	18	30	8	293	1105	3150	3650	840/910		148/153	
10.00-20	18	30	7.5	278	1073	2900	3350	840/910		145/150	
9.00-20	16	25	7	259	1038	2500	2900	810/880		140/145	
8.25-20	16	20	6.5	240	992	2180	2460	840/910	B	135/139	
9.00-16	16	22	6.50H	255	902	1850	2120	730		129/134	
8.25-16	16	18	6.50H	235	867	1600	1800	730	G	124/128	
7.50-16	16	18	6.00G	215	816	1320	1500			118/122	
7.00-16	14	17	5.50F	200	785	1180	1320	730	114/118		
6.50-16	12	18	5.5	185	761	925	1060	630	105/110		
6.50-15	10	18	4.50E	180	742	825	950	530	101/106		
6.00-15	10	13	4.50H	170	717	730	825	530	97/101		
6.00-14	10	13	4.50J	170	691	710	800	530	96/100		
6.00-13	8	13	4.50B	170	666	580	650	420	89/93		



K2009 MINING KING TRUCK TIRE

超大花纹矿山王轮胎

Mining King adopt special formula design, deep tread pattern, big block. Has abrasion, cut-resistance, bomb-resistance, rockfall resistance, little resistance, and energy conservation performance, etc.. Specially for mining area, quarry, construction sites and other hard work condition zones.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)	Speed Index	Load Index	Code
						Dual	Single				
12.00-20	20	32	8.5	315	1145	3450	4000	810/880	G	151/156	K2009
11.00-20	18	30	8	293	1105	3150	3650	840/910		148/153	
8.25-16	16	22	6.50H	235	867	1600	1800	730		124/128	
7.50-16	16	22	6.00G	215	815	1320	1500	730		118/122	
7.00-16	14	21	5.50F	200	785	1180	1320	730		114/118	



H2009 MINING KING & INDUSTRIAL TIRE

工矿用轮胎

For dump trucks on mining and logging service with super cutting resistance.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)	Speed Index	Load Index	Code
						Dual	Single				
12.00-20	20	22	8.5	315	1145	3450	4000	810/800	G	151/156	H2009
11.00-20	18	22	8	293	1105	3150	3650	840/910		148/153	

H2011 (SQ1) MINING STAR TRUCK TYRE

矿山之星系列轮胎

Deep directional design for excellent pulling power in forward and reverse direction.
Heat resistance and abrasion resistance tread.
Strong casing and higher load capacity



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						@10km/h	@50km/h	@10km/h	@50km/h		
13.00-25	22	26	10.00/1.5	350	1350	8000	4250	825	550	TT	H2011 SQ-1
	28					8900	5010	950	740		

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)	Type	Code
						Dual	Single			
12.00-24	20	27	8.5	315	1250	4000	4500	810/880	TT	H2011 SQ-1
12.00-20	20	26	8.5	315	1145	3450	4000	810/880		
11.00-20	18	25	8.0	295	1105	3150	3650	840/910		
10.00-20	18	25	7.5	282	1073	2900	3350	840/910		
9.00-20	16	21	7.0	268	1043	2500	2900	810/880		
8.25-16	16	18	6.50H	235	865	1600	1800	730		
7.50-16	16	18	6.00G	215	830	1320	500	730		

H2012 H2018

MINING KING
& INDUSTRIAL TIRE
工矿用轮胎



H2012

H2018

Specially designed pattern with extra deep tread and compound for long mileage.
Widely reinforced tie bar with both center and shoulder part provides pattern strong property and durability.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						@ 10km/h	@ 50km/h	@ 10km/h	@ 50km/h		
10.00-20	18	30	7.5	278	1073	---	3350	---	910	TT	H2018
11.00-20	18	30	8.0	293	1105	---	3650	---	910		
14.00-20	20	26	10.0	375	1315	7500	4375	700	525		
	28					9000	5135	800	700		
14.00-24	28	32	10.0	375	1420	10000	5600	925	650	TT	H2012 H2018
	36					11000	6640	1050	740		
	40					11500	6900	1100	840		
14.00-25	28	32	10.0	375	1420	10000	5600	925	650	TT	H2012 H2018
	32					11000	6640	1050	740		
	36					11500	6900	1100	840		



TS1000

TIMBER STAR FORESTRY TYRE
林业拖挂车专用轮胎

For dump trucks on forestry logging service.
Deeper tread pattern for powerful traction and longer lifespan

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)	Speed Index	Load Index	Code
						Dual	Single				
12.00-24	20	39	8.5	315	1275	4000	4500	810/880	B	156/160	TS1000

ROCK-X

SUPER OTR AND DUMP TRUCK TYRE
工程车辆和自卸卡车专用轮胎



Strong casing.
Superior in heavy duty & puncture resistant.
Excellent resistance to damage in harsh conditions.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)	Speed Index	Load Index	Code
						Dual	Single				
12.00-24	20	26	8.5	315	1250	4000	4500	810/880	B	156/160	ROCK-X



INDIAN PATTERNS TYRE

印度花纹轮胎



<http://www.honghuatyre.com>

H139 SUPER RIB INDIAN PATTERN TIRE

超级水花系列印度(标准)花纹轮胎

Super heavy duty with special compound and strong carcass structure. Provides long mileage, powerful traction and great resistance to cut and chip.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Code
						Dual	Single	Dual	Single	
11.00-20	18	18.5	8.0	293	1105	3150	3650	840	910	H139
10.00-20	18	18	7.5	285	1085	2900	3350	840	910	
9.00-20	16	18	7.0	265	1045	2500	2900	810	880	
8.25-20	16	16	6.5	235	980	2180	2430	840	910	
7.50-16	16	15	6.00G	215	823	1320	1500	730	730	
7.00-16	14	13	5.50F	200	785	1189	1320	730	730	

H225 MIX LUG INDIAN PATTERN TIRE

混合羊角系列印度(标准)花纹轮胎

Super heavy duty with special compound. Strong extra deep tread ensure powerful traction and give economic efficiency.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Code
						Dual	Single	Dual	Single	
11.00-20	18	22.5	8.0	293	1105	3150	3650	840	910	H225
10.00-20	18	22.5	7.5	283	1080	2900	3350	840	910	
9.00-20	16	22	7.0	268	1045	2500	2900	810	880	
7.50-16	16	18	6.00G	215	825	1320	1500	730	730	
7.00-16	14	15.5	5.50F	202	785	1180	1320	730	730	

H322 MIX RIB (S-LUG) INDIAN PATTERN TIRE

混合水花(半羊角)花纹系列印度(标准)花纹轮胎

Long mileage special with special tread compound and carcass structure. Ensure long mileage with low heat generation and long lasting hard tread.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Code
						Dual	Single	Dual	Single	
12.00-24	20	22.5	8.5	315	1245	4000	4500	810	880	H322
11.00-20	18	22.5	8.0	293	1105	3150	3650	840	910	
10.00-20	18	22.5	7.5	283	1080	2900	3350	840	910	
8.25-20	16	20	6.5	236	992	2180	2430	840	910	
8.25-16	16	19	6.50H	235	867	1600	1800	730	730	
7.50-16	16	18	6.00G	215	825	1320	1500	730	730	

K2018 SUPER LUG INDIAN PATTERN TIRE

超级羊角系列印度(标准)花纹轮胎

Pattern type with wide groove. provides outstanding driving comfort on both unpaved roads and muddy roads.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Code
						Dual	Single	Dual	Single	
11.00-20	18	22.5	8.0	293	1105	3150	3650	840	910	K2018
10.00-20	18	22.5	7.5	283	1080	2900	3350	840	910	
7.50-16	16	22	6.00G	215	816	1320	1500	730	730	
7.00-16	14	21	5.50F	200	785	1180	1320	730	730	
6.50-16	12	18	5.50F	185	761	925	1060	630	630	
6.00-15	10	17.5	4.50E	170	717	825	730	530	630	
6.00-14	10	17	4.50J	170	691	710	800	530	530	
6.00-13	8	15	4.50B	170	666	580	650	420	420	



TRUCK TYRE

卡车轮胎



<http://www.honghuatyre.com>

H881 STD TRAILER TIRE

STD 拖车轮胎

Strong manipulation.
Tread design provides great traction, good handing stability and low resistance.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (lbs)	Pressure (psi)	Type	Code
ST175/80D13	6	6	5.0	177	610	1360	50	TL	H881 STD
ST185/80D13	6	6	5.0	184	626	1480	50		
ST185/80D13	8	6	5.0	184	626	1730	65		
ST205/75D14	6	6	5.5	203	664	1760	50		
ST215/75D14	6	6	5.5	210	678	1870	50		
ST205/75D15	6	6	5.5	200	689	1820	50		
ST225/75D15	8	6	6.0	210	719	2540	65		

H889-1 M/H MOBILE HOME TIRE

移动房屋拖车胎

Using the latest super wear-resistant formula.
Good puncture-resistance.
High lateral skid prevention capability and longer life.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (lbs)	Pressure (psi)	Type	Code
8-14.5	14	6.5	6.0	196	672	3100	115	TL	H889-1 M/H
8-14.5				203	708				
215/60D14.5	14	7	6.0	203	618	3100	110		
235/60D14.5	14	9	7.0	224	673	3500	110		

H889-2 USA MARKET TRAILER TIRE

北美拖车轮胎

Using the latest super wear-resistant formula.
Excellent anti-irregular wear performance and high mileage.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (lbs)	Pressure (psi)	Type	Code
7.50-16	10	6.5	6.0	215	805	2755	75	TL	H889-2
	12					3085	90		
7.00-15	8	6.5	6.0	200	750	1985	60		
	10					2270	75		
ST225/90D16	10	6.5	6.0	215	805	2755	75		
	12					3085	90		
ST205/90D15	8	6.5	6.0	200	750	1985	60		
	10					2270	75		

H889/H889*

TRAILER TIRE FOR PORT
港口码头集装箱拖车轮胎

Using the latest super wear-resistant formula.
Excellent anti-irregular wear performance and high mileage.



H889 H889*

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (lbs)	Pressure (psi)	Type	Code
10.00-20	14	10.5	7.5	278	1055	6170	100	TT	H889
	16					6610	115		
11-22.5	14	10.5	8.25	279	1054	6170	100	TL	H889*
	16					6610	115		

BI 1000 SUPER RIB LIGHT TRUCK TIRE

超级水花轻卡轮胎

Suits for driving on highway and generally paved road.
The unique pattern design and formula design, high quality raw material support.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Speed Index	Load Index	Code
						Dual	Single	Dual	Single			
7.50-17	10	12	5.00F	212	843	1260	1440	550	620	L	116/121	BI1000

H889 RIB TRUCK TIRE

水花花纹系列卡车轮胎

Developed for trucks and buses. Features heat resistant tread.
Required to travel continuously at high speeds on highways.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Load Index	Code
						Dual	Single	Dual	Single		
11.00-20	18	16	8.0	293	1085	3150	3650	840	910	148/153	H889 RIB
10.00-20	18	14	7.5	278	1055	2900	3350	810	880	145/150	
9.00-20	16	14	7.5	259	1018	2500	2900			140/145	
9.00-16	16	16	6.50H	255	890	1720	1955	730		129/134	
8.25-16	16	14	6.50H	235	855	1600	1800			124/128	
7.50-16	14	12	6.00G	215	805	1320	1500			118/122	
7.00-16	14	11	5.50F	200	775	1180	1320	630		114/118	
6.50-16	12	10	5.50F	185	750	925	1060			105/110	
7.00-15	12	11	5.50F	200	750	1030	1150			109/113	
6.50-15	10	10	4.50E	180	730	825	950	530		101/106	
6.50-14	10	10	4.50J	180	705	800	900			100/104	
6.00-15	10	11.5	4.50E	170	705	730	825			97/101	
6.00-14	10	11.5	4.50J	170	680	710	800	420		96/100	
6.00-13	8	11.5	4.50J	170	655	580	650			89/93	

H999 LUG TRUCK TIRE

羊角花纹系列卡车轮胎

The most popular lug tread design for all types of vehicles on both paved and unpaved roads.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Load Index	Code
						Dual	Single	Dual	Single		
12.00-20	20	18	8.5	315	1125	3450	4000	810	880	151/156	H999 LUG
11.00-20	18	16	8	293	1085	3150	3650	840	910	148/153	
10.00-20	18	15	7.5	278	1055	2900	3350	810	880	145/150	
9.00-20	16	15	7.5	259	1018	2255	2575			140/145	
8.25-20	16	14	6.5	235	974	2180	2460	840	910	135/139	
7.50-20	14	14	6	215	935	1655	1885	740	810	126/130	
7.00-20	14	12	5.5	200	904	1550	1750	770	840	123/127	
9.00-16	16	16	6.50H	255	890	1850	2120	730		129/134	
8.25-16	16	14	6.50H	235	855	1600	1800			124/128	
7.50-16	14	11	6.00G	215	805	1320	1500			118/122	
7.00-16	14	11	5.50F	200	775	1180	1320	630		114/118	
6.50-16	12	10	5.50F	185	750	925	1060			105/110	
7.00-15	12	11	5.50F	200	750	1030	1150			109/113	
6.50-15	10	10	4.50E	180	730	825	950	530		101/106	
6.00-15	10	11.5	4.50E	170	705	730	825			97/101	
6.00-14	10	11.5	4.50J	170	680	710	800			96/100	
6.00-13	8	11.5	4.50J	170	655	580	650	420		89/93	



H101 LIGHT TRUCK & JEEPNEY TIRE

轻卡和吉普式公交车用胎

Longer lifespan with wear-resistance compound.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Load Index	Code
						Dual	Single	Dual	Single		
7.50-15	12	11	6.00G	215	780	1215	1360	630	630	115/119	H101 RIB
	14					1285	1450	730	730	117/121	



H318 MUD & RAINFOREST TRUCK/TRAILER TIRE

泥地和雨林卡车/拖车用轮胎

Wide lug & thick tread
For truck or trailer use in mud & rainforest areas.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Load Index	Code
						Dual	Single	Dual	Single		
7.50-16	16	18	6.00G	215	820	1320	1500	730	730	118/122	H318



L210/L306

BOTH ROAD & FIELD USE
路田两用卡车轮胎

For AG trailer, AG truck & AG tractor use

L 210

L 306

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
7.50-16	10	14	6.00G	215	805	1250	530	TT	L210
7.50-16	10	14	6.00G	215	805	1250	530	TT	L306